



HAL
open science

Flow of an elasto-viscoplastic fluid around a blade by means of the FEM with Lagrangian Integration Points (FEMLIP)

Frédéric Dufour, Fiacre Ahonguio, Laurent Jossic

► **To cite this version:**

Frédéric Dufour, Fiacre Ahonguio, Laurent Jossic. Flow of an elasto-viscoplastic fluid around a blade by means of the FEM with Lagrangian Integration Points (FEMLIP). Particles, 2015, Barcelona, Spain. hal-02086391

HAL Id: hal-02086391

<https://hal.univ-grenoble-alpes.fr/hal-02086391>

Submitted on 11 Sep 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Flow of an elasto-viscoplastic fluid around a blade by means of the FEM with Lagrangian Integration Points (FEMLIP)

Frédéric Dufour*, Fiacre Ahonguio[†] and Laurent Jossic[†]

* Univ. Grenoble Alpes, 3SR, F-38000 Grenoble, France
CNRS, 3SR, F-38000 Grenoble, France

e-mail: frederic.dufour@3sr-grenoble.fr, web page: <http://www.3sr-grenoble.fr/spip.php?article441>

[†] Univ. Grenoble Alpes, LRP, F-38000 Grenoble, France
CNRS, LRP, F-38000 Grenoble, France

e-mail: Fiacre.Ahonguio@ujf-grenoble.fr, laurent.jossic@ujf-grenoble.fr
web page: <http://www.laboratoire-rheologie-et-procedes.fr/>

ABSTRACT

Industrial processes include complex fluids often used for specific needs such as dip-coating and removal of objects embedded in those fluids. Therefore, a better understanding of their behaviour may help to better respond to the needs. In this context, this numerical analysis focuses on the creeping flow of a yield stress fluid (carbopol gel) around a blade.

In order to deal with large deformation processes of complex materials in the continuum mechanics framework, the Finite Element Method with Lagrangian Integration Points is used [1]. This method originates from the Particle-In-Cell method for which the numerical integration weight is recomputed in each configuration in order to keep the finite element properties of the Gaussian integration scheme. Indeed, the Lagrangian particles owing all constitutive and history variables are used in a given configuration as integration points in order to compute the nodal velocity field. At the end of a step, the particle positions are updated based on the velocity field and by means of FE shape functions. This method has already been applied to geophysics [2], fresh concrete flow [3] and landslides [4].

Based on the unified constitutive law recently developed in [5], a 3D Herschel-Bulkley model has been implemented in numerical tool based on the FEMLIP. The yield stress is detected by means of the second invariant of the Cauchy stress tensor and the material behaves elastically below the yield stress.

The originality of the study relies on the understanding of the flow properties especially below the yield stress. The numerical results in terms of velocity field and analysis of the unyielded zone are then compared to the experimental results based on PIV measures.

REFERENCES

- [1] L. Moresi, F. Dufour, H. Muhlhaus, "A Lagrangian integration point finite element method for large deformation modeling of viscoelastic geomaterials", *J. of Comp. Phys.*, Vol. 184, 2, p. 476-497 (2003).
- [2] H. Muhlhaus, F. Dufour, L. Moresi, B. Hobbs, "A director theory for viscoelastic folding instabilities in multilayered rock", *Int. J. Solids Struct.*, Vol. 39, 13-14, p. 3675-3691 (2002).
- [3] F. Dufour, G. Pijaudier-Cabot, "Numerical modeling of concrete flow. Homogeneous approach", *Int. J. for Num. Anal. Meth. in Geomech.*, Vol. 29, 4, p.395-416 (2005).
- [4] N. Prime, F. Dufour, F. Darve, "Solid-fluid transition modelling in geomaterials", *Int. J. for Num. and Anal. Meth. in Geomech.*, Vol. 38, 13, p. 1341-1361 (2014)
- [5] N. Prime, F. Dufour, F. Darve, "Unified model for geomaterial solid/fluid states and the transition in between", *Journal of Engineering Mechanics*, Vol. 140, 6 (2014).